

WiFi Made Simple

Our customized, innovative, efficient products are chosen by thousands of heating and cooling professionals. We bring the same level of performance and simplicity to the connected thermostat market with our new line of WiFi thermostats. The T701i is perfect for the everyday homeowner who wants to keep it simple. The T855i is great for all of those advanced jobs that require advanced features, multiple stages or commercial settings.



Exclusively for Contractors



T900 Family



T800 Family



T700 Family



T600 Family

WiFi Optional

Fully functional without internet access. New construction, no password, no problem.



Universal Subbase

No wiring necessary. Fast, easy upgrade from existing Pro1 thermostats.



Technician Private Label

Contractor contact info displayed in mobile app and on the magnetic badge.



Active Alerts

Receive alerts from anywhere. High and low temp. limits, connection status, and more.



Removable Badge System

Heavy duty products for HVAC Professionals




- High Quality**
Pro1 thermostats are contractor grade, built on the proven performance and reliability you expect. It's a difference you can feel.
- One Size Thermostats**
All Pro1 thermostats have the same size footprint, so you never have to worry about wall marks left by old models. You can also upgrade to new models including Wi-Fi without rewiring using the interchangeable subbase system.
- Full Offering**
We offer a full line of thermostats for nearly every application. Whether you need a basic 1 heat, 1 cool non-programmable or a 4 heat, 2 cool Wi-Fi thermostat, Pro1 has you covered.
- Badge System**
All Pro1 thermostats share a removable badge that can easily be replaced with a custom badge that has your contact information. This free service is a great way to generate future business for your company.




Control Remotely



Scheduling



Private Label



Multiple Locations

Are you a **PRO**?



C Commercial 2/4 Time Periods (Occupied/Unoccupied)
7D 7 Day Programmable
5/1/1 5/1/1 Programmable
NP Non-Programmable
5/2 Programming From App

Pro1 Model #

Stages of Heat / Stages of Cool / Gas, Electric or Oil / Heat Pump / Millivolt / Battery Power / 24V Power (Hardwire) / Outdoor Temperature Sensor Compatible / Dual Fuel Compatible / Display Size (Square Inches) / Auto Changeover / Filter Changeover / Room Temperature Calibration / Minimum Compressor Run Time / Compressor Short Cycle Delay / Adjustable Heat & Cool Temperature Swing / Cooling Fan Delay / High/Low Speed Fan Switch / Programmable Fan / Pre-Occupancy Fan / IAQ Fan Mode / Always on Display Light / Keypad Lockout / Adjustable Setpoint Limits / Humidity Control / Memory Type (Permanent) / Touchscreen / Remote Sensor Capable

Terminals

WIFI		Wireless		Wired	
T855i	7D 5/1/1 NP 5/2 C	4*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
T701i	NP**	1	1	•	Rh, Rc, C, Y, W, G, O, B
BEST					
Z955W	7D 5/1/1 NP	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
T955WH	7D 5/1/1 NP C	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D
T631W-2	NP	2	1	•	R, C, Y, W, GH, GL, O/B
BETTER					
T955	7D 5/1/1 NP C	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
T925	7D 5/1/1 NP	3	2	•	R, C, Y, Y2, W2, E, G, O, B, L
T905	7D 5/1/1 NP	1	1	•	Rh, Rc, C, Y, W, G, O, B
T855	7D 5/1/1 NP C	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
T805	7D 5/1/1 NP	1	1	•	Rh, Rc, C, Y, W, G, O, B
T801	NP	1	1	•	Rh, Rc, C, Y, W, G, O, B
GOOD					
T771	NP	0/1	0/1	•	R, C, W/Y, G
T755H	5/1/1 NP	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D
T755S	5/1/1 NP	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2
T755	5/1/1 NP	3*	2	•	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
T725	5/1/1	2	1	•	R, C, Y, W2, E, G, O, B
T721	NP	2	1	•	R, C, Y, W2, E, G, O, B
T715	5/1/1	2	2	•	Rh, Rc, C, Y, Y2, W, W2, G, O, B
T705	5/1/1	1	1	•	Rh, Rc, C, Y, W, G, O, B
T701	NP	1	1	•	Rh, Rc, C, Y, W, G, O, B
BUILDER					
T631-2	NP	2	1	•	R, C, Y, W, GH, GL, O/B
T621-2	NP	2	1	•	R, C, Y, W2, E, G, O, B
T605-2	5/1/1	1	1	•	Rh, Rc, C, Y, W, G, O, B
T601-2	NP	1	1	•	Rh, Rc, C, Y, W, G, O, B

Model # Nomenclature

Prefix
T Thermostats - **DA** Discharge air sensor
R Remote sensor - **Z** Zoning capable

First Number
6 600 platform - **8** 800 platform
7 700 platform - **9** 900 platform

Second Number
0 Single stage - **3** Universal PTAC
1 Multi stage gas - **5** Universal multi stage
2 Multi stage heat pump - **7** Heating or cooling

Third Number
1 Non-Programmable
5 Programmable

Suffix
W Wireless - **S** Wired Remote Sensor Capable
H Humidity Control - **-2** Series Number
i Internet Capable

COMPATIBLE WITH		COMPATIBLE WITH			
Z2K955WDA	Two Zone Kit	Zoning Models	WW160W	Wireless Wire	24V
RZ251W	Secondary Zone Controller - Wireless Remote Sensor	Z955W - T955WH	R250S	Wired Outdoor Temperature Sensor	T755S
RZ250W	Wireless Outdoor Sensor	Z955W - T955WH	R251S	Wired Indoor Temperature Sensor	T755S
Z260W	Damper Module	Z955W	T150	Stat Guard Cover	Any Thermostat
ZDA250W	Discharge Air Sensor	Z955W	T119	Universal Wall Plate	Any Thermostat
W150W	Wireless Repeater	Wireless Models	E219	Weather Resistant Junction Box	Any Model

Stages * = 2 Stages for conventional heat - Programming ** = Programming only available from the web app