2 Years Labor/10 Years Parts Warranty



Top Motch
QUALITY
Best
WARRANTY





2 Years Labor/10 Years Parts-Limited Warranty

*See complete warranty for details

Benefits:

Performance and Efficiency

Super Sized Evaporator Coil

This is where efficiency begins (4 sided design) Higher Performance in colder weather Largest in the Industry

100% Full Flow Titanium Turbo Heat Exchanger

Features:

Lifetime warranty against corrosion 100% Titanium Turbo design for maximum heat transfer into your pool All 2" plumbing to maintain efficient full water flow

Ultra-Quiet 825rpm Fan Motor

Ultra-Quiet and efficient operation only 56db

Thermal Expansion Valve

Sensible Automation

Refrigerant regulated for maximum efficiency in all types of weather

Reverse Gas defrost allows heating in conditions below freezing Units can also cool the pool

Chill Buster (optional)

Intelligent Control and Design

Capable of automating your pool/spa combo Controls valves and thermostat operation Compatible with all external automation

Solar Ready Differential Control

Automate your solar pool heating for the perfect hybrid system Maximizes efficiency and control

Advanced Diagnostic LCD Display

Notifies you of potential service issues in real words -not codes Back lit display, multiple languages, and digital lockout standard

Even Heat

Override the timer to maintain your desired temperature anytime

Triple Thermostat

Individual controls for pool, spa and solar thermostats

Durable ABS Cabinet

Rattle free. Rust proof. UV protected for lifetime durability

State of the Art Manufacturing

Helium (He) Testing

Factory leak detection 100 times more accurate than our competitors ensuring optimized performance

Mass Flow Charging

Computerized refrigerant filling with no human error Accurate to 1/100th of an ounce ensuring each unit is "Perfect"

Interlocked testing Stations

Computerized quality control testing process can't be bypassed

Final Run Test

Tests every component, in every unit, every time A "Perfect" unit every time for the ultimate piece of mind

Units Specs	HE 90	HE 110	HE 125	HE 150
BTU/COP*Outside of AHRI 1160 Test Standard	90,000/6.3	110,000/6.4	120,000/6.3	136,000/6.0
AHRI High Test Point	84,000/5.8	99,000/6.0	109,000/5.9	124,000/5.4
AHRI Low Test Point	56,000/4.0	66,000/4.1	74,000/4.1	85,000/4.0
Min Amps/Max Breaker	36/40	37/40	37/50	37/50
Weight	210 LBS	218 LBS	218 LBS	222 LBS
(Shipping)	(245 LBS)	(253 LBS)	(253 LBS)	(257 LBS)
Dimensions	31x31x34	31x31x38	31x31x38	31x31x38
(Shipping)	(33x31x39)	(33x31x43)	(33x31x43)	(33x31x43)









